



## Press Release:

February, 2019



### **Solstice 4.0 and Gen3 Hardware Platform**

Mersive Solstice 4.0 along with our new Gen3 hardware platform take meeting collaboration and productivity to new heights serving as the ubiquitous platform for the modern meeting space and includes features that support freedom when sharing large amounts of content throughout a meeting.

#### **New in Solstice 4.0 and Gen 3 Pod**

- More processing power for improved wireless content sharing performance including simultaneous 4k streams.
- WIRED INPUT – Simultaneous HDMI-input allows hard-wired content sources to add a collaborative content stream directly into a Solstice session with other wireless sources.
- DUAL DISPLAY – Two HDMI outputs that can be configured to mirror or extend. In extended mode, Users can post content across two displays to support more posts in view.
- SOLSTICE INK – Collaborate seamlessly with wireless highlighting and markup from anywhere in the room using a smartphone.
- Gigabit Ethernet with PoE+ support or DC 12V @ 2A max.
- USB-C input to support future innovation.
- International language support is expanded to 16 different languages.
- Customizable welcome screen instructions.

# Gen3 Pod Hardware and Technical Specs



## Hardware Ports

- Gigabit Ethernet with PoE+ support
- Power connector, DC 12V at 2Amps
- 2x HDMI out supporting up to one 4K display or two 1080p displays
- HDMI in
- Stereo out, 8-channel 7.1 surround sound
- 2x USB 3.0
- USB-C (for future features)

## Dimensions

<b>Hardware Type</b>	Compute Console
<b>Size</b>	184.2mm x 86.2mm x 26.3mm
<b>Weight</b>	0.75lbs

## Technical Specifications

<b>Processor</b>	Qualcomm Snapdragon™ 820, quad-core Kryo™ CPU
<b>Graphics Processor</b>	Adreno™ 530
<b>Internal Storage</b>	4GB RAM, 16GB eMMC Flash Storage
<b>Ethernet</b>	RJ45 Gigabit
<b>Wireless</b>	Dual band, 802.11ac 2x2 MIMO
<b>Streaming Video Support</b>	4K (4096 x 2160), HD (1920x1080), SD (1280x720)
<b>Output</b>	HDMI 2.0 for HDMI1, HDMI 1.4 for HDMI2 with Audio, Stereo output (8-channel 7.1 surround sound)
<b>Input</b>	HDMI 1.4b
<b>I/O</b>	2x USB 3.0, USB-C port
<b>Operating Temperature (Ambient)</b>	0° C (32° F) to 50° C (122° F)
<b>Power Input</b>	PoE+ or DC 12V @ 2A max
<b>Power Efficiency Level</b>	VI
<b>Adaptor</b>	Switching 100-240VAC, 50/60Hz, changeable plug type (international support)
<b>Adaptor Region Support</b>	US, EU, AK, AUS
<b>Warranty</b>	Limited 1-year manufacturer's hardware warranty

## Testing and Certifications

<b>Safety</b>	UL
<b>Emissions Testing</b>	FCC, CE (Home and Office Use)
<b>Accessibility</b>	WCAG 2.0 AA Compliant. Full VPAT document available <a href="#">here</a> .